

Suntherm high efficiency air handlers are designed to heat and cool your home quietly and efficiently. These units have been engineered with variable speed ECM blower motors and cabinets made of heavy gauge, rust resistant steel for durability. Suntherm high efficiency air handlers can be properly matched with various brands of condensing units to increase SEER and HSPF ratings resulting in greater energy savings.

MMVE HYDRONIC AIR HANDLERS

- Designed For Maximum Performance
- High BTU output at low water temperatures
- Ideal for Combi Systems
- 4-Way multiposition
- Variable speed ECM motor
- Pump Contacts
- Dry Contacts for boiler operation
- Pump Timer
- Dehumidification option
- Supports 2 stage outdoor units
- Electric heat options available

Model	Nominal	Unit Dim (in)	BTU Output (EWT)	
	Tons	H x W x D	140°F	180°F
MMVEOS	1.5 - 2.0	29 X 17.5 X 21	42,000	67,000
MMVEOM	1.5 - 3.0	29 X 21 X 21	56,000	90,000
MMVEOL	3.5 - 5	29 X 24 1/2 X 21 3/4	82,000	131,000





MSVE HYDRONIC/DX COOLING AIR HANDLERS

- · 4-Way multipostion
- · Variable speed ECM motor
- · Contacts for pump
- · Dry contacts for Boiler operation
- Factor y inst alled TXV
- · Electric heat option available
- · Hot water / Chilled water option available

Unit Dim (in) H x W x D	BTU Outpı 140°F	ıt (EWT) 180°F
43 x17.5 x 21	26,000	41,000
48 x 21 x 21	44,000	70,000
58.75 x 24.5 x 21.75	67,000	106,000
58.75 x 24.5 x 21.75	75,000	119,000
	H x W x D 43 x17.5 x 21 48 x 21 x 21 58.75 x 24.5 x 21.75	H x W x D 140°F 43 x17.5 x 21 26,000 48 x 21 x 21 44,000 58.75 x 24.5 x 21.75 67,000

Product specifications subject to change without notice



www.ecovisionsales.ca